# LLumar® iLLusions™ Decorative Window Film Specialty Series

# **Black (NRMM PS2)**





# **Specifications**

Product Name	Black (NRMM PS2)	
Product Series	Specialty Series	
Film Type	Polyester	
Adhesive Type	Pressure-sensitive	
Usage	Interior	
Widths	60", 48"	
Film Thickness (excludes liner)	.002"	

LLumar.com/decofilmviewer

Performance Data	% Visible Light Transmittance	% Diffuse Visible Light Reflectance (exterior)	Privacy Film Rating
Clear Glass 1/8" (3mm) single pane	90	8	0
Black (NRMM PS2) 1/8" (3mm) single pane	0	5*	10

<sup>\*</sup>This reflectance value is a standard specular reflectance value For the most current data please go to LLumar.com/nar-deco-specs

### **Product Description**

LLumar specialty films can mask light, add privacy or give a pop of color to any space. Bold, graphic hues and distinctive designs enliven retail spaces and commercial properties. Unique combinations of specialty films allow for endless customizable possibilities.

#### Benefits and selection criteria

- Ideal when complete darkness is required for functional space
- · Blocks views for complete privacy
- Ideal for dark room or media room applications
- Simulates black glass for a fraction of the cost of the real thing
- Helps shield harmful ultraviolet rays

## Installation and Warranty

LLumar iLLusions are professionally installed by a global network of authorized dealers in accordance with factory procedures. While installation is fast, with minimal disruption to tenants or contractors, the film is extremely durable and is backed by a limited manufacturer's warranty. Your dealer can provide you with technical information and warranty details.

#### Contact Information

Call 1-800-851-7781 or visit

solutions.llumar.com/commercial to learn more.

#### Privacy Film Rating

This number, between 0 (clear) and 10 (opaque), represents the relative difficulty an observer has in identifying the nature and character of an object located on the opposite side of the window, with the observer and the object both located at least 2 feet from the pane upon which the product has been installed.









