
## LLumar® iLLusions™ Decorative Window Film Gradient Series **Mirrored Mini Dot Matrix Gradient**





# **Specifications**

Product Name	Mirrored Mini Dot Matrix Gradient
Product Series	Gradient Series
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Width	60"
Film Thickness (excludes liner)	.002"
Coordinating Product	Dusted Frost Film

#### % Diffuse Performance Location Visible Light on Film % Visible Light Reflectance Privacy Film Data (see diagram) Transmittance Rating (exterior) Clear Glass 90 8 0 1/8" (3mm) single pane (1)Mirrored Mini Dot Matrix Gradient (2)

For the most current data please go to LLumar.com/nar-deco-specs

LLumar.com/decofilmviewer

### **Product Description**

Gradient series window films are available in unique designs to fit the needs of different spaces. These window films are intended to give graduated privacy while still allowing for a sense of openness. Partially block out views, selectively hide unattractive areas or add a fresh design element with this versatile series.

#### Benefits and selection criteria

- Creates interest and function without interference
- Etched frost finish heightens composition

for privacy

- Detailed View
- Helps shield harmful ultraviolet rays

· Ideal for bathrooms with a center band

## Installation and Warranty

LLumar iLLusions are professionally installed by a global network of authorized dealers in accordance with factory procedures. While installation is fast, with minimal disruption to tenants or contractors, the film is extremely durable and is backed by a limited manufacturer's warranty. Your dealer can provide you with technical information and warranty details.

### Contact Information

Call 1-800-851-7781 or visit solutions.llumar.com/commercial to learn more.

### **Privacy Film Rating**

This number, between 0 (clear) and 10 (opaque), represents the relative difficulty an observer has in identifying the nature and character of an object located on the opposite side of the window, with the observer and the object both located at least 2 feet from the pane upon which the product has been installed.



ΕΛSTΜΛΝ Il umar.com © 2014 Eastman Chemical Company. LLumar® and the LLumar® logo are trademarks of Eastman Chemical Company or one of its wholly owned subsidiaries. (11/14)As used herein, @ denotes registered trademark status in the U.S. only. Printed in U.S.A.